

Attenuation Pluggerz earplugs Uni-Fit

FILTER	FREQ.	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	SNR	H	M	L
MUSIC	A	17.7	19.0	19.1	18.3	22.2	30.5	28.9	27.1	22	24	18	16
	S	5.5	3.5	4.6	3.5	3.8	4.3	3.1	3.8				
	APV	12.2	15.5	14.5	14.8	18.4	26.2	25.8	23.3				
SLEEP	A	25.1	24.8	23.7	23.9	27.1	32.4	37.7	37.9	27	28	24	21
	S	4.5	3.8	4.6	3.4	3.3	4.2	6.7	8.0				
	APV	20.6	21.0	19.1	20.5	23.8	28.2	31.0	29.9				
WATER	A	17.3	18.9	21.1	22.7	27.3	31.0	31.9	32.2	25	27	22	19
	S	3.1	4.4	3.4	4.0	4.2	3.6	5.7	3.7				
	APV	14.2	14.2	17.7	18.7	23.1	27.4	26.2	28.5				
TRAVEL	A	25.6	26.4	25.5	26.5	27.9	31.8	30.1	30.3	27	27	25	23
	S	4.8	3.0	2.5	3.8	2.4	3.3	4.4	6.5				
	APV	20.8	12.4	14.2	16.6	24.5	30.3	26.2	37.4				

Attenuation Pluggerz hearing Protector:

A Average attenuation in dB

S Standard deviation in dB

APV Assumed protection value in dB

SNR Single number rating

H Protection value in high frequencies in dB

M Protection value in medium frequencies in dB

L Protection value in low frequencies in dB